



PREGLJED SUSTAVA

HSI 150/KES MA 150

UNUTARNJA STRANA



Razdjeljeni brtveni element sa priteznim profilima iz poliamida za kabele od Ø 10-112mm (HSI 150-DG)



Toploskupljajući brtveni element za kabele
1x Ø 25-78mm HSI 150 D1x80 ili
3x Ø 22-56mm HSI 150 D3x58 ili
7x Ø 12-31mm HSI 150 D7x33



Razdjeljena gumena brtva sa priteznim profilima iz nehrđajućeg čelika za kabele (HRD 150/160 G z/d) max 3x Ø 60mm ili 5x Ø 47mm ili 9x Ø 33mm (preporučeno za HSI 150 GSM)




HVS protupožarni jastučići za kabele klasa S 90 u kombinaciji sa sustavom HSI 150 prema DIN 4102-9


ZID



HSI 150 K/X
Jednostruka zidna uvodnica



HSI 150 K/X
Dvostruka zidna uvodnica




HSI 150 K/K2 AF/X
Zidna uvodnica sa prirubnicom za bitumenski premaz



HSI 150 DFK
Prirubnica za montažu preko prodora u betonu



HSI 150 FLFE/X
DIN 18533 dvostruka zidna uvodnica sa fiksnom/prigradnom prirubnicom




HSI 150 K/K2 S. °S/X
zidna uvodnica sa uvodom pod kutom



HSI 150 GSM/X
Jednostruka zidna uvodnica sa utičnom spojnicom za cijevi

Ostale mogućnosti na upit!

VANJSKA STRANA



Brtveni element za rebraste cijevi (sa nehrđajućim prstenom za utore cijevi)
HSI 150 MA110 WR (Ø 110mm)
HSI 150 MA125 WR (Ø 125mm)
HSI 150 MA168 WR (Ø 160mm)



Brtveni element za glatke cijevi
HSI 150 MA110 GR (Ø 110mm)
HSI 150 MA125 GR (Ø 125mm)
HSI 150 MA145 GR (Ø 140mm)
HSI 150 MA168 GR (Ø 160mm)




Brtveni element za glatke cijevi sa utičnom manžetom
HSI 150 Dx110 GSM (Ø 110mm), HSI 150 D1x125 GSM (Ø 125mm)
HSI 150 D 160 GSM (Ø 160mm)




Brtveni element sa manžetom za Hateflex 14150 (Ø 160mm) zaštitne kabele KES MA 150 D



SEGMENTO sustav za kabele Ø 5-31mm



Razdjeljeni brtveni element sa priteznim profilima iz poliamida za kabele od Ø 10-112mm (HSI 150-DG)



Toplo ili hladno skupljajući brtveni element za kabele
1x Ø 25-78mm HSI 150 D1x80 ili
3x Ø 22-56mm HSI 150 D3x58 ili
7x Ø 12-31mm HSI 150 D7x33
za cijevi
rebraste zaštitne cijevi za kabele Ø 75-125mm (hladnoskupljajući princip brtvljenja)
HSI 150 D110 KS, HSI 150 D125 KS



Razdjeljena gumena brtva sa priteznim profilima iz nehrđajućeg čelika za kabele (HRD 150/160 G z/d) max 3x Ø 60mm ili 5x Ø 47mm ili 9x Ø 33mm



Glatke cijevi
Ø 110mm, Ø 125mm, Ø 160mm



Hauff-Technik GmbH & Co. KG

Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de

Zastupnik za Hrvatsku

EL SIS d.o.o.

Benkovićeva 4A
HR-10000 Zagreb

Tel. +385 1 2430 262
Mob. +385 98 312 969

www.elsis.hr
elsis@elsis.hr